韶关东森合成材料有限公司
Shaoguan Dongsen Synthetic Material Co., Ltd.

TECHNICAL DATA SHEET

MDI Moisture-Curing Hardener DXCM-75

PRODUCT FEATURES

High gloss and hardness, good flexibility, good cost-effectiveness, good abrasion resistance, and strong intercoat adhesion. Suitable for professional floor coatings, sealer primers and clear varnishes in one- and two-component polyurethane systems.

APPLICATIONS

Suitable for floor coatings, sealer primers and wood coatings. It can be used alone or in combination with general alkyd resins and acrylic resins.

PRODUCT SPECIFICATIONS

Item	Specification	Unit	Test Method
Appearance	Water-clear to slightly yellow transparent viscous liquid	/	GB/T 1721-2008
(Fe-Co) Color Number	≤1	/	GB/T 1722-1992
NCO Content	7.0±0.5	%	Q/SGDS 01-2026
Solid Content	75.0±2.0	%	GB/T 1725-2007
Viscosity (Rotational Viscometer, 25°C)	5000±1000	mPa·s	GB/T 9751.1-2008

USE INSTRUCTIONS

1. This product contains organic solvents. Appropriate personal protective measures should be taken during use.

PACKAGING AND STORAGE

1. Supplied in 10 kg, 20 kg, 60 kg and 200 kg steel drums, or in customized packaging.
2. Store in a cool, well-ventilated place. Keep the container tightly closed and away from heat and ignition sources. Shelf life is 9 months in sealed packaging.

Disclaimer: This Product Data Sheet has been prepared based on actual testing and production experience using advanced testing equipment. However, variations in application conditions and material combinations are beyond our control. Users should therefore conduct appropriate tests, trials and evaluations according to their actual needs and intended use before applying this product. The company assumes no liability for losses or risks arising from the user's use of this product.
Official website: www.doxu.com.cn