SHAOGUAN DONGSEN SYNTHETIC MATERIAL CO., LTD.
TECHNICAL DATA SHEET

【TYPE】 WD-6200

【CHARACTERIC ADVANTAGES】
Low viscosity, zero VOC, used as a two-component coating hardener, excellent chemical resistance and weather resistance, outstanding gloss retention and excellent mechanical properties.

【APPLICATIONS】
Used as hardener or coating material adhesive, suitable for the coating of original car paint, car repair, transportation vehicles, industrial products and plastics.

【SPECIFICATION】

PRODUCT / SPECIFICATION	WD-6200
APPERANCE	Colorless to pale yellow transparent viscous liquid
COLOR (Pt-Co)	≤40
NCO %	22.5~23.5%
Free-HDI %	≤0.25
SOLID CONTENT %	100%
VISCOSITY / /25℃ (CPS)	850~1350

【PRECAUTIONS】
1. Can be diluted with urethane grade solvents PMA (propylene glycol methyl ether acetate), PGDA (propylene glycol diacetate), PC (propylene carbonate), etc.
2. Extremely sensitive to air humidity. When opening or in small packages, please prevent moisture from entering, seal it immediately after use or use it as soon as possible.
3. It must be kept in a cool and dry place and no outdoors. The shelf life is 9 months in the sealed package (from the date of delivery).

【PACKAGE】
20KG, 60KG, 230KG iron drum or customized.

DISCLAIMER OF RESPONSIBILITY:
The main information and the data were from our advanced testing equipment according to actual testing and production experience, however, the different working environment and materials when the product is applied are beyond the control range of the our company. Therefore, we strongly recommends that users must test, experiment and trial according to actual needs and uses before actually application. If you have any technical problems, please pass the info to our technical dept.
★We only guarantees the quality and stability of the product itself.