SHAOGUAN DONGSEN SYNTHETIC MATERIAL CO., LTD.

TECHNICAL DATA SHEET

【TYPE】 WD-8980

【CHARACTERIC ADVANTAGES】

Good hydrophilicity and are easy to emulsify, good hand-stirring properties, high gloss, good fullness, good transparency, and excellent chemical resistance.

【APPLICATIONS】

Water-based two-component polyurethane coating for wood paint, industrial paint, floor paint, crosslinking agent, etc.

【SPECIFICATION】

Polymer type: hydrophilic polyisocyanate prepolymer

PRODUCT / SPECIFICATION	WD-8980
APPERANCE	Colorless to pale yellow transparent viscous liquid
COLOR (Fe-Co)	≤1
NCO %	14.0~16.0%
Free-HDI %	≤0.3
SOLID CONTENT %	80%
VISCOSITY / /25℃ (CPS)	100~500

【PRECAUTIONS】

1. Can be diluted with urethane grade solvents PMA (propylene glycol methyl ether acetate), PGDA (propylene glycol diacetate), PC (propylene carbonate), etc.
2. Extremely sensitive to air humidity. When opening or in small packages, please prevent moisture from entering, seal it immediately after use or use it as soon as possible.
3. It must be kept in a cool and dry place and no outdoors. The shelf life is 6 months in the sealed package (from the date of delivery).

【PACKAGE】

20KG, 60KG, 215KG iron drum or customized.

DISCLAIMER OF RESPONSIBILITY:

The main information and the data were from our advanced testing equipment according to actual testing and production experience, however, the different working environment and materials when the product is applied are beyond the control range of the our company. Therefore, we strongly recommends that users must test, experiment and trial according to actual needs and uses before actually application. If you have any technical problems, please pass the info to our technical dept.

★We only guarantees the quality and stability of the product itself.